THE PROPOSED RIGHT OF WAY SHALL BE REFERENCED FROM THE CENTERLINE OF S.R. 374. REFERENCE MONUMENT AND RIGHT OF WAY MONUMENTS ARE SHOWN ON STANDARD CONSTRUCTION DRAWING MC-1 (REV. 6-13-69) OF THE OHIO DEPARTMENT OF TRANSPORTATION. THE PLACING OF THE MONUMENTS SHALL BE UNDER THE DIRECTION OF THE OF A REGISTERED SURVEYOR, AND ARE TO BE SET, AS SHOWN BY THE CONTRACTOR AT THE TIME OF CONSTRUCTION. ANY ALTERATIONS, WITH PRIOR APPROVAL OF THE OHIO DEPARTMENT OF TRANSPORTATION, SHALL BE NOTED AND O.D.O.T. SHALL BE NOTIFIED OF THE NEW LOCATIONS (SURVEY OPERATIONS MANAGER.) THE ACCURACY SHALL BE +/- 0.02 FOOT. MONUMENTS TO BE SET DURING CONSTRUCTION DISTANCE FROM & NUMBER OF SURVEY STATION RIGHT LEFT 30.00 2 30.00 96+00.00 2 50.00 50.00 PC 97+21.42 50.00 2 50.00 PT 99+32.00 30.00' PC 102+15.67 29.84 102+25.93 TOTAL: * QUANTITY CARRIED TO GENERAL SUMMARY SHEET **LEGEND** = CENTERLINE REFERENCE MONUMENT

0

0

0

HOCKING COUNTY BENTON TOWNSHIP

SECTION 13 TOWNSHIP 11N RANGE 18W

NOTE: THE EXISTING RIGHT OF WAY WIDTH AND LOCATION WERE DETERMINED USING:

